



Applications:

Ideal for security lighting for walkway, entrance, residential and more.


Specification & features:

- Rigid aluminum die-cast back mounting plate.
- Durable polyester powder coating finish with PC prismatic lens diffuser.
- UV stabilized polycarbonate prismatic refractor.
- Photocell-Optional.
- UL1598/CUL listed, Suitable for wet location.

WM01 Series:

Item No.	Lamp&Watt.	Lamp Base	Voltage	Ballast Type	Finish	Photocell	Certified
WM01-35HPS	HPS35W	E26	120V	R-NPF	BN/WT	Optional	UL/CUL
WM01-50HPS	HPS50W	E26	120V	R-NPF	BN/WT	Optional	UL/CUL
WM01-70HPS	HPS70W	E26	120V	R-NPF	BN/WT	Optional	UL/CUL
WM01-E26PLC	PLC26W	G24q-3	120V	NPF	BN/WT	Optional	N/A
WM01-13PLS	PLS13W	GX23	120V	NPF	BN/WT	Optional	UL/CUL
WM01-26PLS	2xPLS13W	GX23	120V	NPF	BN/WT	Optional	UL/CUL
WM01-E42PLT	PLT42W	GX24q-4	120V	NPF	BN/WT	Optional	UL/CUL
WM01-E42PLT	PLT42W	GX24q-4	120V _{thru} 277V	HPF	BN/WT	Optional	UL/CUL

Note: BN = Architectural Bronze, WT = White



Installation:

- Quick Installation and Maintenance.
- Suitable for mounting to standard 3" or 4" junction box, 1/2" conduit, or directly onto flat surface. (See our installation sheet.)