



Applications:

Ideal for area and security lighting for perimeters of roadside, residential backyard.

Specification & features:

- Rigid aluminum die-cast housing.
- UV stabilized Prismatic acrylic refractor.
- One piece hydro-formed aluminum reflector.
- 4KV pulsed rated porcelain socket.
- Twist-lock Photocell.
- External slip fitter is adjustable for 1-1/4" to 2" pipe, (Extension Pipe not included.)
- UL1598/CUL listed, Suitable for wet location.

WM02 Series:

Item No.	Lamp&Watt.	Lamp Base	Voltage	Ballast Type	Finish	Photocell	Certified
WM02-100MV	MV100W	E26	120V	HX-NPF	Nature	Included	UL/CUL
WM02-125MV	MV125W	E26	120V	HX-NPF	Nature	Included	UL/CUL
WM02-175MV	MV175W	E39	120V	HX-NPF	Nature	Included	UL/CUL
WM02-35HPS	HPS35W	E26	120V	R-NPF	Nature	Included	UL/CUL
WM02-50HPS	HPS50W	E26	120V	R-NPF	Nature	Included	UL/CUL
WM02-70HPS	HPS70W	E26/E39	120V	R-NPF	Nature	Included	UL/CUL
WM02-E65CFL	CFL65W	E26	120V	NPF	Nature	Included	N/A

Optional accessories: Grill guard and extension Pie, Please refer page CC04004-10012002-B087.

