



### Applications:

Ideal for use on security and area lighting for perimeters of roadside, back yard, rural areas.

### Specification & features:

- Rigid aluminum die-cast housing.
- 4KV pulse rated porcelain socket.
- UV stabilized prismatic acrylic refractor.
- Single piece hydro-formed aluminum reflector.
- Twist-lock photocell.
- External slip fitter is adjustable for 1-1/4" to 2" extension pipe.(Extension Pipe is Optional.)
- UL1598/CUL Listed, Suitable for wet location.

### WM03 Series:

Item No.	Lamp&Watt.	Lamp Base	Voltage	Ballast Type	Finish	Photocell	Certified
WM03-100MV	MV100W	E26	120V	HX-NPF	Nature	Included	UL/CUL
WM03-125MV	MV125W	E26	120V	HX-NPF	Nature	Included	UL/CUL
WM03-175MV	MV175W	E39	120V	HX-NPF	Nature	Included	UL/CUL
WM03-70HPS	HPS70W	E26/E39	120V	R-NPF	Nature	Included	UL/CUL
WM03-100HPS	HPS100W	E26/E39	120V	R-NPF	Nature	Included	UL/CUL
WM03-150HPS	HPS150W	E26/E39	120V	R-NPF	Nature	Included	UL/CUL

Optional accessories: Grill guard and extension Pie, Please refer page CC04004-10012002-B087.

