



QH-215



QH-225



QH-1005



QH-505



QH-815



QH-825



QH-850

Applications:

Ideal for machinery and car repair, plumbing work, construction site and much more.

Floor-stand Series:

- Rigid aluminum die-cast housing and frame.
- Durable polyester powder coating finish .
- Fully tempered glass lens and wire guard to ensure the safety operation.
- Foam covered handle for firmed grip.
- Energy saving aluminum reflector.
- UL/CUL listed, Suitable for wet location.
- GS/TUV,CE,NEMKO,IP20,IP44,approved.
- On-Off switch(optional).

Clamp-on Series:

- Rigid aluminum die-casting housing and frame.
- Durable polyester powder coated finish .
- Fully tempered glass lens and wire guard to ensure the safety operation.
- Easy clamp-on with heavy-duty hook and clamp.
- UL/CUL listed, Suitable for wet location.
- GS/TUV,CE,NEMKO,IP20,IP44,approved.
- On-Off switch(optional).

Item No.	Max Watt.	Lamp Base	Voltage	Bulb Size	Color	Certified
QH-215	J-150W	R7S	120V-240V	78mm	YL/BK	UL/CUL,GS/TUV,CE
QH-225	J-250W	R7S	120V-240V	78mm	YL/BK	GS/TUV,CE
QH-505	J-500W	R7S	120V-240V	118mm	YL/BK	UL/CUL,GS/TUV,CE
QH-1005	J-1500W	R7S	120V-240V	254mm	BK	GS/TUV,CE
QH-815	J-150W	R7S	120V-240V	78mm	YL/BK	UL/CUL,GS/TUV,CE
QH-825	J-250W	R7S	120V-240V	78mm	YL/BK	UL/CUL
QH-850	J-250W	R7S	120V-240V	78mm	YL/BK	UL/CUL,GS/TUV,CE

NOTE : YL = YELLOW, BK = BLACK.