



Applications:

Suitable for all portable lighting applications for both indoor and outdoor. Ideal for machinery and car repair, plumbing work, construction site, rescue projects and more.

Specification and Features:

QH-511BU/QH-521BU

- QH-511BU: Single 500W halogen fixture unit.
- QH-521BU: Double 500W halogen fixture units.
- Rigid aluminum die-cast housing and frame.
- Durable polyester powder coating finish .
- Fully tempered glass lens and wire guard to ensure the safety operation.
- Compact folded umbrella legs for easy carry & storage.
- UL/CUL listed, Suitable for wet location.
- GS/TUV, CE, NEMKO, IP20, IP44 approved.
- Equipment (optional):
 - Cord storage hook.
 - On-Off switch.

Specification and Features:

QH-211BT/QH-221BT

- QH-211BT: Single 250W halogen fixture unit.
- QH-221BT: Double 250W halogen fixture units.
- Rigid aluminum die-cast housing and frame.
- Durable polyester powder coated finish .
- Fully tempered glass lens and wire guard to ensure the safety operation.
- Compact folded umbrella legs for easy carry & storage.
- UL/CUL listed, Suitable for wet location.
- GS/TUV, CE, NEMKO, IP20, IP44 approved.
- Equipment (optional):
 - Cord storage hook.
 - On-Off switch.

Item No.	Max Watt.	Lamp Base	Voltage	Stand.	Color	Certified
QH-521BU	2xJ-500W	R7S	120V-240V	Umbrella	YL/BK	UL/CUL,GS/TUV,CE,NEMKO
QH-511BU	J-500W	R7S	120V-240V	Umbrella	YL/BK	UL/CUL,GS/TUV,CE,NEMKO
QH-221BT	2xJ-250W	R7S	120V-240V	Trigger	YL/BK	UL/CUL,GS/TUV,CE,NEMKO
QH-211BT	J-250W	R7S	120V-240V	Trigger	YL/BK	UL/CUL,GS/TUV,CE,NEMKO

NOTE : YL = YELLOW, BK = BLACK.